



1010...

LOIRA

CHECK VALVES



- Loira check valve
- Female thread: ISO 228
- Temperature range: 0°C to +90°C

This valve is particularly indicated for use in non-return systems with generally non-corrosive fluids that are compatible with the valve materials. Excellent fields of application are in plant engineering for plumbing and heating, industry, agriculture and pneumatics.

The direction of flow is indicated by an arrow on the valve body. It can be installed in any position.

Seat seal is provided by a NBR gasket.

COMPONENTS:

POSN.	PART NAME	No. Pcs.	MATERIAL
1	Body	1	CW617N UNI-EN 12165
2	End connection	1	CW617N UNI-EN 12165
3	Spring	1	AISI 302 stainless steel
4	Valve	1	Nylon
5	Gasket	1	NBR

DIMENSIONS:

DN	A	B	C	PN
10	3/8"	34	49	12
15	1/2"	34	49	12
20	3/4"	42	54	12
25	1"	48	59	12
32	1.1/4"	60	67	10
40	1.1/2"	69	72	10
50	2"	95	77	10
65	2.1/2"	102	98	8
80	3"	125	103	8
100	4"	154	119	8

PACKAGING:

	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
CODE	10100003	10100004	10100006	10100008	10100010	10100011	10100013	10100015	10100017	10100019
PIECES PER BOX	25	25	20	12	6	5	3	-	-	-
PIECES PER CARTON	250	250	200	120	72	50	30	20	15	12